## Crimping Pump Electric Hydraulic pe-nut

## **30 cu. in./min** Two-Speed

Extremely durable yet lightweight. Operates under low-line voltage conditions.

## PE-NUT PUMP — 115V

- 5/8 hp universal electric motor (50/60 cycle)
- Two-stage pump for rapid ram advanceOperational under low-line
- voltage conditions
- Optional operating pressures available; consult Power Team for details
- Designed for use with spring-returned remote tools
- High-pressure safety relief valve
- · Remote hand control with 10-foot cord
- Carrying handle
- · Factory filled oil reservoir
- Pressure matched quick-coupler supplied
- Optional carrying case

The PE-NUT Series High-Pressure Hydraulic Power Pumps are extremely durable yet lightweight and operate under low-line voltage conditions. The two-stage pumping system of these unique, intermittent duty pumps is designed for years of dependable service. These pumps incorporate a pistontype high-pressure pump supercharged by a low-pressure pump.



Pump Model	Oil Delivery per min.	Oil Reservoir qt.	Usable Oil qt.	Overall Width in.	Overall Length in.	Overall Depth in.	Pump Weight w/Oil Ibs.
PE-NUT PE-NUT-C* (	160 in <sup>3</sup> @ 100 psi 30 in <sup>3</sup> @ 10,000 psi	1.61	0.75	6.5	14.38	8.25	28

Electrical Data					
Electric Motor	Electrical Control				
5/8 hp, 10,000 rpm 115V AC, 50/60 Hz 11 amp current draw (115V @ 10,000 PSI)	Remote control with 10-foot cord				

\*Includes Case



186